

absolute
precision
guidance

SATLOC M3

- Accurate Swath Guidance
- Optional Touchscreen
- Various Screen Sizes
- View previous spray areas
- Ruggedized modular design
- L-Band/WAAS compatible receiver



Precision GPS Guidance Applications



positioned for **your success**

GENERAL / PERFORMANCE SPECIFICATIONS

- Real time graphic swathing display capable of showing precise swath deposition, field boundaries, and mark points.
- Various mounting choices for easy installation
- "As applied" map when using Satloc Variable Rate Control software
- Job and spray/area recall
- Multi-function "Ruggedized" light bar for exterior mounting and "heads-up" visibility
- Remote Color Active Matrix Display
- Optional Resistive Touchscreen capability on display
- Automatic zoom and pan control when option selected
- Multiple field storage
- Log file replay feature: review of application work on the job and spray resume
- Real time display of acres in area and product applied
- System diagnostics and configuration display for DGPS
- NMEA output port for running other peripheral equipment
- Over 1000 hours of data logging storage for use with SATLOC Mapstar planning and analysis software
- Windows 98®

SATLOC MAPSTAR SOFTWARE

- View log files for information on jobsite or in the office
- Mission Planning
- Create or edit Waypoints, Field Boundaries and Patterns
- Latitude and longitude positioning
- Area sprayed and chemical amounts applied
- Works with all Windows® compatible printers
- Import ESRI Shape, DXF and MID/MIF file formats
- Converts ESRI Shape, DXF and MID/MIF file formats to Satloc job files
- Export Satloc logs to ESRI Shape, DXF, MID/MIF or ASCII file formats
- SATLOC background map underlay
- Measure distance and area

VEHICLE MOUNTING

- Ruggedized universal swivel RAM mount for 8.4" display
- ISO-mounted shock mount support for CPU module
- Remotely mounted CPU module for installation flexibility

M3 COMPUTER GENERAL SPECIFICATIONS

Processor type:	Pentium class MMX, 233 MHz
Memory:	64MB SDRAM standard
Operating system:	DOS/*Windows 98®
Storage:	6.1 Gigabyte
Storage (Removable):	Single PCMCIA slot
Display:	6.4" or 8.4" TFT active matrix color Sunlight readable, low-glare screen NEMA 4 sealed enclosure
HiBrite:	Technology with 8.4" screen
Connections:	Power, Lightbar, DGPS Receiver, Keypad or keyboard/mouse GPIO (swath advance, spray on/off, aux.), COM1 RS-232 (full handshaking), Display power, VGA
Size:	CPU: 9.375" x 6.5" x 4.1875" Display: 2" x 9.5" x 7.625" (8.4) Display: 2" x 13.5" x 8.875" (12.1)
Weight:	6.9 pounds, CPU only
Power:	Range 10-36 volts DC, reverse polarity and over voltage protection
Nominal Power:	38W to 55W (dependent on display size)
Operating Temperature:	System: -22°F to 140°F (-30°C to +60°C) Display only: -4°F to 40°F (-20°C to +60°C)
Housing:	Tough extruded aluminum construction Dust proof, waterproof, shock resistant, fully sealed

SLXg3 RECEIVER

- Dimensions: 7.5" L x 4.9" W x 2.0" H
- 4 diagnostics LEDs
- 12 channel GPS engine
- 5Hz position update rate
- RS-232 interface
- Acquisition: first fix in <90 seconds (typical)
- NMEA 0183 output
- L-Band/WAAS differential GPS

SATLOC M3

Official Satloc Dealer

Telephone: (480)348-9919
Fax: (480)348-6370
7560 E. Redfield Rd • Suite B
Scottsdale • AZ • USA • 85260

www.satloc.com

Avery label #05260 (laser print)